

INTERNATIONAL  
STANDARD

IEC  
**60384-3**  
QC 300800

Third edition  
2006-10

Fixed capacitors for use in electronic equipment –

**Part 3:  
Sectional specification: Surface mount fixed  
tantalum electrolytic capacitors with manganese  
dioxide solid electrolyte**

IECNORM.COM : Click to view the full document  
IEC 60384-3:2006



Reference number  
IEC 60384-3:2006(E)

## Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

## Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

## Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site ([www.iec.ch](http://www.iec.ch))**
- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site ([www.iec.ch/searchpub](http://www.iec.ch/searchpub)) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications ([www.iec.ch/online\\_news/\\_justpub](http://www.iec.ch/online_news/_justpub)) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: [cusiserv@iec.ch](mailto:cusiserv@iec.ch)  
Tel: +41 22 919 02 11  
Fax: +41 22 919 03 00

# INTERNATIONAL STANDARD

IEC  
**60384-3**  
QC 300800

Third edition  
2006-10

## Fixed capacitors for use in electronic equipment –

**Part 3:  
Sectional specification: Surface mount fixed  
tantalum electrolytic capacitors with manganese  
dioxide solid electrolyte**

IECNORM.COM : Click to view the full document

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

U

*For price, see current catalogue*

## CONTENTS

FOREWORD .....	4
1 General .....	6
1.1 Scope.....	6
1.2 Object .....	6
1.3 Normative references .....	6
1.4 Information to be given in a detail specification .....	6
1.5 Terms and definitions .....	7
1.6 Marking .....	8
2 Preferred ratings and characteristics .....	9
2.1 Preferred characteristics .....	9
2.2 Preferred values of ratings .....	10
3 Quality assessment procedures .....	11
3.1 Primary stage of manufacture.....	11
3.2 Structurally similar components .....	11
3.3 Certified records of released lots .....	11
3.4 Qualification approval.....	11
3.5 Quality conformance inspection.....	12
4 Test and measurement procedures.....	13
4.1 Preliminary drying .....	13
4.2 Measuring conditions .....	13
4.3 Mounting .....	13
4.4 Visual examination and check of dimensions .....	14
4.5 Electrical tests.....	14
4.6 Resistance to soldering heat .....	15
4.7 Solderability .....	16
4.8 Shear test .....	16
4.9 Substrate bending test .....	17
4.10 Rapid change of temperature .....	17
4.11 Climatic sequence (applicable to Style 1 capacitors only).....	17
4.12 Damp heat, steady state (applicable to Style 1 capacitors only).....	18
4.13 Characteristics at high and low temperature .....	18
4.14 Surge .....	18
4.15 Endurance .....	19
4.16 Reverse voltage (if required by the detail specification).....	19
4.17 Component solvent resistance (if required by the detail specification) .....	20
4.18 Solvent resistance of the marking (if required by the detail specification) .....	20
4.19 High surge current (if required by the detail specification) .....	20
Annex A (normative) Test plans for assessment level EZ .....	21
Annex B (normative) Test schedule for assessment level EZ .....	24

Table 1 – Category voltages .....	10
Table 2 – Test temperatures .....	19
Table A.1 – Test plan for qualification approval – Assessment level EZ .....	21
Table A.2 – Test plan for quality conformance inspection – Lot-by-lot tests – Assessment level EZ .....	22
Table A.3 – Test plan for quality conformance inspection – Periodic tests – Assessment level EZ .....	23
Table B.1 – Test schedule for qualification approval – Assessment level EZ .....	24

IECNORM.COM : Click to view the full PDF of IEC 60384-3:2006

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT -

**Part 3: Sectional specification: Surface mount fixed tantalum electrolytic capacitors with manganese dioxide solid electrolyte**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-3 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This third edition cancels and replaces the second edition published in 1989 and constitutes a minor revision related to tables, figures and references.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1771/FDIS	40/1789/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The QC numbers that appear on the front cover of this publication are the specification numbers in the IEC Quality Assessment System for Electronic Components (IECQ).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60384 series, under the (new) general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of January 2007 have been included in this copy.

IECNORM.COM : Click to view the full PDF of IEC 60384-3:2006

## FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

### Part 3: Sectional specification: Surface mount fixed tantalum electrolytic capacitors with manganese dioxide solid electrolyte

#### 1 General

##### 1.1 Scope

This specification applies to surface mount tantalum solid electrolyte capacitors. These capacitors are primarily intended to be mounted directly onto substrates for hybrid circuits or onto printed boards.

The following two styles are considered:

- Style 1: protected capacitors;
- Style 2: unprotected capacitors.

##### 1.2 Object

The object of this standard is to prescribe preferred ratings and characteristics and to select from IEC 60384-1:1999, the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor.

##### 1.3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60062, *Marking codes for resistors and capacitors*

IEC 60063, *Preferred number series for resistors and capacitors*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60384-1, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60410, *Sampling plans and procedures for inspection by attributes*

ISO 3, *Preferred numbers – Series of preferred numbers*

##### 1.4 Information to be given in a detail specification

Detail specifications shall be derived from the relevant blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example, by an asterisk.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

#### 1.4.1 Outline drawing and dimensions

The detail specification shall give an illustration of the capacitor as an aid to easy recognition and for comparison of the capacitor with others. Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given. All dimensions are to be stated in mm.

NOTE The information given in 1.4.1 may for convenience be presented in tabular form.

Normally, the numerical values shall be given for the length, width and height of the body. When necessary, for example, when a number of case sizes are covered by a detail specification, the dimensions and their associated tolerances shall be placed in a table below the drawing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor.

#### 1.4.2 Mounting

The detail specification shall give guidance on methods of mounting for normal use. Mounting for test and measurement purposes (if required) shall be in accordance with 4.3.

#### 1.4.3 Ratings and characteristics

The ratings and characteristics shall be in accordance with the relevant clauses of this specification, together with the following.

##### 1.4.3.1 Rated capacitance range

See 2.2.1.

NOTE When products approved to the detail specification have different ranges, the following statement should be added: "The range of values available in each voltage range is given in the qualified products list (QPL).".

##### 1.4.3.2 Particular characteristics

Additional characteristics may be listed, when they are considered necessary, to specify adequately the component for design and application purposes.

##### 1.4.3.3 Soldering

The detail specification shall prescribe the test methods, severities and requirements applicable for the solderability test and the resistance to soldering heat test.

#### 1.4.4 Marking

The detail specification shall specify the content of the marking on the capacitor and on the package. Deviations from 1.5 of this sectional specification shall be specifically stated.

### 1.5 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60384-1, as well as the following, apply.

#### 1.5.1

##### surface mount capacitor

capacitor whose small dimensions and nature or shape of terminations make it suitable for surface mounting in hybrid circuits and on printed boards

### 1.5.2 rated voltage

$U_R$

See 2.2.16 of IEC 60384-1

NOTE 1 The sum of the d.c. voltage and the peak a.c. voltage applied to the capacitor should not exceed the rated voltage.

NOTE 2 For short periods, however, the rated voltage may be exceeded (see 2.2.5 and 4.14).

### 1.5.3

#### Class 1

capacitor with low dielectric losses and high stability of capacitance; Ta powders with low volumetric capacitance values are used

### 1.5.4

#### Class 2

capacitor with a dielectric of medium range volumetric capacitance for applications where low losses and high stability of capacitance are not of major importance

### 1.5.5

#### Class 3

capacitor with a dielectric of high volumetric capacitance for applications where small size and high capacitance values are essential, and higher losses and less stability of capacitance can be tolerated

## 1.6 Marking

See 2.4 of IEC 60384-1, with the following details.

**1.6.1** The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- a) polarity of the terminations (unless identified by the construction);
- b) rated capacitance, in clear or coded form;
- c) rated voltage, in clear or coded form, (d.c. voltage may be indicated by the symbol (  $----$  or  $---$  ),
- d) tolerance on rated capacitance;
- e) style (in accordance with 1.1);
- f) year and month (or week) of manufacture;
- g) manufacturer's name or trade mark;
- i) climatic category;
- j) manufacturer's type designation;
- k) reference to the detail specification.

**1.6.2** Surface mount capacitors are generally not marked on the body. If some marking can be applied, they shall be clearly marked with as many as possible of the above items as is considered useful. Designation of polarity is a mandatory item. Any duplication of information in the marking on the capacitor should be avoided. Where space does not permit the marking of the capacitor in accordance with IEC 60062 the following code may be used.

### a) Capacitance coding

The rated capacitance value in picofarad is given by the following digit and letter code.

Letter	Value
A	1,0
C	1,2
E	1,5
G	1,8
J	2,2
L	2,7
N	3,3
Q	3,9
S	4,7
U	5,6
W	6,8
Y	8,2

Digit	Multiplier
9	$10^{-1}$
0	$10^0$
1	$10^1$
2	$10^2$
3	$10^3$
4	$10^4$
5	$10^5$
6	$10^6$
7	$10^7$
8	$10^8$

### b) Voltage coding

For code letters for marking, see the detail specification.

**1.6.3** Any marking shall be legible and not easily smeared or removed by rubbing with the finger.

**1.6.4** The package containing the capacitor(s) shall be clearly marked with all the information listed in 1.5.1, except polarity, unless this is applicable to the method of packing.

**1.6.5** Any additional marking shall be so applied that no confusion can arise.

## 2 Preferred ratings and characteristics

### 2.1 Preferred characteristics

The values given in detail specifications shall preferably be selected from the following.

#### 2.1.1 Preferred climatic categories

The capacitors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1.

The lower and upper category temperature and the duration of the damp heat, steady state test shall be chosen from the following.

Lower category temperature:	–55 °C.
Upper category temperature:	+85 °C and +125 °C.
Duration of the damp heat, steady state test:	Style 1: 21 and 56 days Style 2: --

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

## 2.2 Preferred values of ratings

### 2.2.1 Rated capacitance ( $C_R$ )

Preferred values of rated capacitance are 1,0 – 1,5 – 2,2 – 3,3 – 4,7 – 6,8 and their decimal multiples.

These values conform to the E6 series of preferred values given in IEC 60063.

### 2.2.2 Tolerance on rated capacitance

The preferred tolerances on the rated capacitance are  $\pm 10\%$  and  $\pm 20\%$ .

### 2.2.3 Rated voltage ( $U_R$ )

The preferred values of rated direct voltages taken from the R5 series of ISO 3 are:

1,0 – 1,6 – 2,0 – 2,5 – 3,5 – 4,0 – 5,0 – 6,3 and their decimal multiples.

If other values are required they shall preferably be chosen from the R10 series.

### 2.2.4 Category voltage ( $U_c$ )

For capacitors having an upper category temperature of  $125\text{ }^\circ\text{C}$ , category voltages are given in Table 1.

Table 1 – Category voltages

$U_R$ V	2,5	4	6,3	10	16	25	40	63	100
$U_c$ V	1,6	2,5	4,0	6,3	10	16	25	40	63

### 2.2.5 Surge voltage

The surge voltage shall be  $1,3 \times$  the rated or  $1,3 \times$  the category voltage, rounded off to the nearest volt.

### 2.2.6 Rated temperature

The standard value of the rated temperature is  $85\text{ }^\circ\text{C}$ .

### 2.2.7 Requirements for Class 1, Class 2 and Class 3

The detail specification shall provide the maximum value for the dissipation factor ( $\tan \delta$ ), preferably as listed below.

Class 1       $\leq 0,08$

Class 2       $\leq 0,12$

Class 3       $\leq 0,24$

NOTE The requirements depend on the type of powder, the rated voltage and the case size of capacitors. See the following examples for typical combinations of case size, capacitance and rated voltage.

Class	3216-18* size	6,3 V; 10 $\mu$ F	Ta powder ( $\mu$ FV/g)
Class 1	6,3 V 15 $\mu$ F	3216-18*	< 30 000
Class 2	6,3 V 33 $\mu$ F	2012-12*	< 70 000
Class 3	6,3 V 68 $\mu$ F	1608-09*	< 100 000

Size code structure (3D) *LW-H*

where

*L* is the nominal dimension in units of 0,1 mm;

*W* is the nominal dimension in units of 0,1 mm;

*H* is the maximum dimension in units of 0,1 mm.

### 3 Quality assessment procedures

#### 3.1 Primary stage of manufacture

The primary stage of manufacture is the forming of the tantalum oxide dielectric.

#### 3.2 Structurally similar components

Capacitors considered as being structurally similar are capacitors produced with similar processes and materials, though they may be of different case sizes and values.

#### 3.3 Certified records of released lots

The information required in 3.9 of IEC 60384-1 shall be made available when prescribed in the detail specification and when requested by a purchaser. After the endurance test, the parameters for which variables information is required are the capacitance change,  $\tan \delta$  and the leakage current.

#### 3.4 Qualification approval

The procedures for qualification approval testing are given in 3.5 of IEC 60384-1.

The schedule to be used for qualification approval testing on the basis of lot-by-lot and periodic tests is given in 3.5 of this specification. The procedure using a fixed sample size schedule is given in 3.4.1 and 3.4.2.

##### 3.4.1 Sampling

The fixed sample size procedure is described in 3.5.3b) of IEC 60384-1. The sample shall be representative of the range of capacitors for which approval is sought. This may or may not be the complete range covered by the detail specification. The sample shall consist of specimens having the lowest and highest voltages and, for these voltages, the smallest and largest case size. When there are more than four case sizes an intermediate case size shall also be tested. In each of these case size/voltage combinations (values), the highest capacitance shall be chosen. Thus, for the approval of a range, testing is required of either four or six values. When the range consists of less than four values, the number of specimens to be tested shall be that required for four values.

Spare specimens are permitted as follows:

Two (for six values) or three (for four values) per value, which may be used as replacements for specimens which are non-conforming because of incidents not attributable to the manufacturer.

The numbers given in Group 0 assume that all groups are applicable. If this is not so, the numbers may be reduced accordingly.

When additional groups are introduced into the qualification approval test schedule, the number of specimens required for Group 0 shall be increased by the same number as that required for the additional groups.

Table A.1 gives the number of samples to be tested in each group or subgroup together with the permissible number of non-conforming items for qualification approval tests.

### 3.4.2 Tests

The complete series of tests for selected assessment level given in Tables A.1 to A.3 and the test schedule given in Annex B are required for the approval of capacitors covered by one detail specification. The tests of each group shall be carried out in the order given.

The whole sample shall be subjected to the tests of Group 0 and then divided for the other groups.

Non-conforming specimens found during the tests of Group 0 shall not be used for the other groups.

"One non-conforming item" is counted when a capacitor has not satisfied the whole or a part of the tests of a group.

Approval is granted when the number of non-conforming items does not exceed the specified number of permissible non-conforming items for each group or subgroup and the total number of permissible non-conforming items.

NOTE 1 Tables A.1 and B.1 together form the fixed sample size test schedule. Annex A includes the details for sampling and the permissible non-conforming items for the different tests or groups of tests, whereas Annex B, together with the details of tests contained in Clause 4, gives a complete summary of test conditions and performance requirements indicating where, for example for the test method or conditions of test, a choice should be made in the detail specification.

NOTE 2 The conditions of test and performance requirements for the fixed sample size test schedule should be identical to those prescribed in the detail specification for quality conformance inspection.

## 3.5 Quality conformance inspection

### 3.5.1 Formation of inspection lots

#### 3.5.1.1 Groups A and B inspection

These tests shall be carried out on a lot-by-lot basis according to test plan for selected assessment level in Table A.2.

A manufacturer may aggregate the current production into inspection lots subject to the following safeguards:

- 1) the inspection lot shall consist of structurally similar capacitors (see 3.2);
- 2a) the sample tested shall be representative of the values and dimensions contained in the inspection lot:
  - in relation to their number;
  - with a minimum of five of any one value;
- 2b) if there are less than five of any one value in the sample the basis for the drawing of samples shall be agreed between the manufacturer and the National Supervising Inspectorate.

### 3.5.1.2 Group C inspection

These tests shall be carried out on a periodic basis according to the test plan for selected assessment level given in Table A.3.

Samples shall be representative of the current production of the specified periods and shall be divided into small, medium and high sizes. In order to cover the range of approvals in any period, one voltage shall be tested from each group of sizes. In subsequent periods other sizes and/or voltage ratings in production shall be tested with the aim of covering the whole range of approval.

### 3.5.2 Test schedule

The test schedule for qualification approval is given in Annex B.

### 3.5.3 Delayed delivery

When, according to the procedures of 3.10 of IEC 60384-1, re-inspection has to be made, solderability, capacitance and leakage current shall be checked as specified in Group A and B inspection.

### 3.5.4 Assessment levels

The assessment level(s) given in the blank detail specification shall preferably be selected from Tables A.2 to A.3.

## 4 Test and measurement procedures

This clause supplements the information given in Clause 4 of IEC 60384-1.

### 4.1 Preliminary drying

If prescribed in the detail specification for Style 2 capacitors, the conditions given in 4.3 of IEC 60384-1 apply.

### 4.2 Measuring conditions

Capacitors of Style 2 shall be measured at a relative humidity of 25 % to 75 % maximum.

### 4.3 Mounting

See 4.33 of IEC 60384-1.

#### 4.3.1 Mounting conditions

The detail specification shall specify the soldering process to be used.

#### 4.3.2 Final inspection, measurements and requirements

The capacitors shall be visually examined and measured and meet the requirements of Annex B.

#### 4.4 Visual examination and check of dimensions

See 4.4 of IEC 60384-1, with the following details.

##### 4.4.1 Visual examination

Visual examination shall be carried out with suitable equipment with approximately 10 $\times$  magnification and lighting appropriate to the specimen under test and the quality level required.

NOTE The operator should have facilities available for incident or transmitted illumination as well as an appropriate measuring facility.

##### 4.4.2 Requirements

The capacitors shall be examined to verify that the materials, design, construction, physical dimensions and workmanship are in accordance with the applicable requirements given in the detail specification.

#### 4.5 Electrical tests

##### 4.5.1 Leakage current

See 4.9 of IEC 60384-1, with the following details.

###### 4.5.1.1 Measuring conditions

The rated voltage shall be applied across the capacitor and its protective resistor. The protective resistor shall have a value of 1 000  $\Omega$ .

###### 4.5.1.2 Requirement

The leakage current at 20 °C shall not exceed  $0,02 C_R U_R \mu\text{A}/(\mu\text{F}\times\text{V})$  or 1  $\mu\text{A}$ , whichever is the greater.

##### 4.5.2 Capacitance

See 4.7 of IEC 60384-1, with the following details.

###### 4.5.2.1 Measuring conditions

The capacitance shall be measured at a frequency of 100 Hz or 120 Hz, as specified in the detail specification. The peak alternating voltage actually applied across the capacitor terminations shall not exceed 0,5 V a.c. r.m.s.

A d.c. bias voltage of

- 1,1 V to 1,5 V for types with a rated voltage of  $\leq 2,5$  V
- 2,1 V to 2,5 V for types with a rated voltage of  $> 2,5$  V

may be applied during the measurement.

The inaccuracy of the measuring instruments shall not exceed  $\pm 2$  % of the specified limit, whether this is given as an absolute value or as a change of capacitance.

NOTE Measurement without a polarizing voltage is optional.

#### 4.5.2.2 Requirement

The capacitance shall correspond with the rated value taking into account the tolerance.

#### 4.5.3 Tangent of loss angle ( $\tan \delta$ )

See 4.8.1 of IEC 60384-1, with the following details.

##### 4.5.3.1 Measuring conditions

The measurement shall be made under the conditions of 4.5.2. The inaccuracy of the measuring equipment shall not exceed 0,01 absolute value.

##### 4.5.3.2 Requirement

The tangent of loss angle (at 20 °C) shall not exceed the limits specified in the detail specification.

#### 4.5.4 Impedance (if applicable)

See 4.10 of IEC 60384-1, with the following details.

##### 4.5.4.1 Measuring conditions

The ambient temperature shall be  $(20 \pm 2) ^\circ\text{C}$ . The a.c. value of the measuring voltage shall not exceed 0,5 V a.c. r.m.s. The frequency of the measuring voltage shall be 100 kHz.

The error of measurement shall not exceed  $\pm 10\%$  of the requirement.

##### 4.5.4.2 Requirement

The impedance shall meet the requirements of the detail specification.

#### 4.5.5 Equivalent series resistance (ESR) (if required by the detail specification)

See 4.8.2 of IEC 60384-1, with the following details.

##### 4.5.5.1 Measuring conditions

The ambient temperature shall be  $(20 \pm 2) ^\circ\text{C}$ . The a.c. value of the measuring voltage shall not exceed 0,5 V a.c. r.m.s. A d.c. bias voltage of 2,1 V to 2,5 V may be applied during the measurement. The frequency of the measuring voltage shall be 100 kHz.

The error of measurement shall not exceed 10% of the requirement.

##### 4.5.5.2 Requirements

The ESR shall meet the requirements of the detail specification.

#### 4.6 Resistance to soldering heat

See 4.14 of IEC 60384-1, with the following details.

##### 4.6.1 Initial measurement

The capacitance and the tangent of loss angle shall be measured according to 4.5.2 or 4.5.3.

#### 4.6.2 Test conditions

The detail specification shall prescribe the test method and the test conditions.

a) Solder bath method

Immersion attitude

Temperature and immersion time

b) Reflow method

Reflow temperature profile

#### 4.6.3 Final inspection, measurements and requirements

The capacitors shall be visually examined and measured and shall meet the following requirements.

Under normal lighting and approximately 10× magnification there shall be no signs of damage such as cracks.

The capacitance and tangent of loss angle shall be measured. They shall not exceed the limits specified in the detail specification.

### 4.7 Solderability

See 4.15 of IEC 60384-1, with the following details.

#### 4.7.1 Test conditions

The detail specification shall prescribe the test method and the test conditions.

a) Solder bath method

Temperature and immersion time

b) Reflow method

Reflow temperature profile

#### 4.7.2 Final inspection, measurements and requirements

The capacitor shall then be visually examined under normal lighting and approximately 10× magnification. There shall be no signs of damage.

The areas and edges to be examined as defined in the detail specification shall be covered with a smooth and bright solder coating with no more than a small amount of scattered imperfections such as pinholes or un-wetted or de-wetted areas. These imperfections shall not be concentrated in one area.

### 4.8 Shear test

See 4.34 of IEC 60384-1.

#### 4.8.1 Initial requirements

Not required (see Group 3).

#### 4.8.2 Final measurements and requirements

The capacitors shall be visually examined and measured and meet the requirements of Annex B.

#### 4.9 Substrate bending test

Not applicable to surface mounting capacitors which, according to their detail specification, shall only be mounted on alumina substrates.

See 4.35 of IEC 60384-1, with the following details.

##### 4.9.1 Initial measurements

Not required (see Group 3).

##### 4.9.2 Test conditions

The detail specification shall prescribe the amount of deflection and the number of bends.

##### 4.9.3 Final measurements and requirements

The capacitors shall be visually examined and measured and meet the requirements of Annex B.

#### 4.10 Rapid change of temperature

See 4.16 of IEC 60384-1, with the following details.

##### 4.10.1 Initial measurement

Not required (see Group 3)

##### 4.10.2 Conditioning

The capacitors shall be subjected to test Na for 5 cycles. The duration of the exposure at each temperature limit shall be 30 min. The recovery period shall be 1 h to 2 h.

##### 4.10.3 Final measurements and requirements

After recovery the capacitors shall be measured and shall meet the requirements shown in Annex B.

#### 4.11 Climatic sequence (applicable to Style 1 capacitors only)

See 4.21 of IEC 60384-1, with the following details.

##### 4.11.1 Initial measurement

Not required.

##### 4.11.2 Dry heat

See 4.21.2 of IEC 60384-1.

##### 4.11.3 Damp heat, cyclic, test Db, first cycle

See 4.21.3 of IEC 60384-1.

##### 4.11.4 Cold

See 4.21.4 of IEC 60384-1.

#### **4.11.5 Damp heat, cyclic, test Db, remaining cycles**

See 4.21.6 of IEC 60384-1.

##### **4.11.5.1 Recovery**

1 h to 2 h.

#### **4.11.6 Final inspection, measurements and requirements**

The capacitors shall be visually examined and measured and shall meet the requirements shown in Annex B.

#### **4.12 Damp heat, steady state (applicable to Style 1 capacitors only)**

See 4.22 of IEC 60384-1, with the following details.

The capacitors shall be mounted according to 4.3.

##### **4.12.1 Initial measurement**

Not required (see Group 3).

##### **4.12.2 Conditions of test**

No voltage shall be applied.

##### **4.12.3 Final inspection, measurements and requirements**

After recovery for 1 h to 2 h, the capacitors shall be visually examined and measured and shall meet the requirements shown in Annex B.

#### **4.13 Characteristics at high and low temperature**

See 4.29 of IEC 60384-1, with the following details.

The capacitors shall be mounted according to 4.3.

##### **4.13.1 Measurements and requirements**

The capacitors shall be measured and shall meet the requirements shown in Annex B.

#### **4.14 Surge**

See 4.26 of IEC 60384-1, with the following details.

##### **4.14.1 Test procedure**

The capacitors shall be subjected to 1 000 cycles each consisting of a charge as described below, followed by a discharge period of 5 min 30 s.

A voltage, equal to the surge voltage, shall be applied during 30 s through a resistor with a value so that the total resistance in series with the capacitor and voltage source is  $1\ 000\ \Omega \pm 100\ \Omega$ .

The test shall be made at the following temperatures.

**Table 2 – Test temperatures**

Upper category temperature	Test temperature
85 °C	All specimens at upper category temperature
125 °C	50 % of the specimens at 85 °C and the remaining 50 % at the upper category temperature

Each surge voltage cycle shall be performed in such a manner that the capacitor is discharged through the resistor of approximately 1 000 Ω at the end of the 30 s application.

The test shall be terminated on the discharge portion of the cycle.

#### 4.14.2 Final measurements and requirements

The capacitors shall be measured and shall meet the requirements given in Annex B.

### 4.15 Endurance

See 4.23 of IEC 60384-1, with the following details.

The capacitors shall be mounted according to 4.3.

#### 4.15.1 Initial measurement

Not required (see Group 3).

#### 4.15.2 Conditions of test

Duration:	2 000 h
Test temperature:	Upper category temperature.
Applied voltage:	Category voltage, unless otherwise specified in the detail specification

NOTE When the category voltage and/or temperatures is/are different from the rated voltage and/or temperatures, the sample tested is divided into two parts and submitted to the rated and category voltages and temperatures respectively.

The test voltage shall be applied gradually (not less than 2 min but not more than 5 min) either by a slow build-up of voltage or through a resistor which shall be shorted out within 5 min. The impedance of the voltage source seen from the terminations of each capacitor shall not exceed 3 Ω.

Storage batteries or an electronic power supply, capable of supplying at least 1 A when a capacitor is shorted, shall be used.

#### 4.15.3 Final inspection, measurements and requirements

After recovery for 1 h to 2 h, the capacitors shall be visually examined and measured and shall meet the requirements shown in Annex B.

### 4.16 Reverse voltage (if required by the detail specification)

#### 4.16.1 Initial measurement

Not required (see Group 3).

#### 4.16.2 Conditions of test

The capacitors shall be subjected to the conditions under a) followed by the conditions under b).

a)	Test temperature:	Upper category temperature
	Applied voltage:	3 V d.c. or 10 % of the rated voltage, whichever is less, in the reverse polarity direction, unless otherwise specified in the detail specification
	Duration:	125 h

b)	Test temperature:	Upper category temperature
	Applied voltage:	Direct voltage equal to the category voltage in the forward polarity direction
	Duration:	125 h

#### 4.16.3 Final measurements and requirements

After recovery the capacitors shall be visually examined and measured and shall meet the requirements given in Annex B.

#### 4.17 Component solvent resistance (if required by the detail specification)

See 4.31 of IEC 60384-1.

#### 4.18 Solvent resistance of the marking (if required by the detail specification)

See 4.32 of IEC 60384-1.

#### 4.19 High surge current (if required by the detail specification)

According to 4.39 of IEC 60384-1, with the following details:

##### 4.19.1 Initial measurements

Not required.

##### 4.19.2 Final measurements and requirements

Final measurements and requirements are those for the subsequent tests in Group 0 or in the blank detail specification in Group A, as appropriate.

## Annex A

(normative)

### Test plans for assessment level EZ

**Table A.1 – Test plan for qualification approval – Assessment level EZ**

Group	Clause number and test <sup>a</sup>	Number of specimens ( <i>n</i> ) and acceptance criteria ( <i>c</i> )		
		<i>n</i> <sup>d</sup>	<i>c</i>	<i>c</i> total
0	4.19 High surge current (if required by the detail specification) 4.4 Visual examination 4.4 Dimensions 4.5.1 Leakage current 4.5.2 Capacitance 4.5.3 Tangent of loss angle 4.5.4 Impedance <sup>c</sup> 4.5.5 Equivalent series resistance <sup>c</sup> Spare specimens	124 16	0	0
1A	4.6 Resistance to soldering heat 4.17 Component solvent resistance <sup>c</sup>	12	0	0
1B	4.7 Solderability 4.18 Solvent resistance of the marking <sup>c</sup>	12	0	0
2	4.9 Substrate bending test <sup>e</sup>	12	0	0
3	4.3 Mounting <sup>b</sup> 4.4 Visual examination 4.5.1 Leakage current 4.5.2 Capacitance 4.5.3 Tangent of loss angle 4.5.4 Impedance <sup>c</sup> 4.5.5 Equivalent series resistance <sup>c</sup>	88	0	0
3.1	4.8 Shear (adhesion) test 4.10 Rapid change of temperature 4.11 Climatic sequence (Style 1 only)	20	0	0
3.2	4.12 Damp heat steady state (Style 1 only)	20	0	0
3.3	4.15 Endurance	20	0	0
3.4	4.13 Characteristics at high and low temperature	12	0	0
3.5A	4.14 Surge voltage	8	0	0
3.5B	4.16 Reverse voltage <sup>c</sup>	8	0	0

<sup>a</sup> Refers to Clause 4 of this specification.

<sup>b</sup> The specimens found to be non-conforming after mounting shall not be taken into account when calculating the permitted non-conforming items for the following tests. They should be replaced by spare capacitors.

<sup>c</sup> If required by the detail specification.

<sup>d</sup> For capacitance/voltage combinations, see 3.4.1.

<sup>e</sup> Not applicable to surface mounting capacitors which according to their detail specification shall be mounted on alumina substrates.

**Table A.2 – Test plan for quality conformance inspection –  
Lot-by-lot tests – Assessment level EZ**

Group	Clause number and test <sup>a</sup>	Inspection level <i>IL</i>	Sample size <i>n</i>	Acceptance number <i>c</i>
A0	4.19 High surge current (if required by the detail specification) 4.5.1 Leakage current 4.5.2 Capacitance 4.5.3 Tangent of loss angle 4.5.4 Impedance <sup>e</sup> 4.5.5 Equivalent series resistance <sup>e</sup>		100 % <sup>b</sup>	
A1	4.4 Visual examination 4.4 Dimensions <sup>c</sup>	S3	<sup>d</sup>	0
B1	4.7 Solderability 4.18 Solvent resistance of the marking <sup>e</sup>	S3	<sup>d</sup>	0

<sup>a</sup> Refers to Clause 4 of this specification.

<sup>b</sup> 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million. The sampling level shall be established by the manufacturer. The calculation of ppm values shall be made in accordance with CECC 00 014 counting any parametric failure as a non-conforming item. In the case where one or more non-conforming items occur in a lot, this lot shall be rejected.

<sup>c</sup> This test may be replaced by in-production testing, if the manufacturer installs SPC on dimensional measurements or other mechanisms to avoid parts exceeding the limits.

<sup>d</sup> Number to be tested: Sample size as directly allotted to the code letter for IL in Table 2A of IEC 60410 (single sampling plan for normal inspection).

<sup>e</sup> If required by the detail specification.

IECNORM.COM : Click to view the full PDF of IEC 60384-3:2006

**Table A.3 – Test plan for quality conformance inspection –  
Periodic tests – Assessment level EZ**

Group	Clause number and test <sup>a</sup>	Periodicity (months)	Total sample size <i>n</i>	Acceptance number <i>c</i>
C1	4.6 Resistance to soldering heat 4.17 Component solvent resistance <sup>d</sup>	3	12	0
C2	4.9 Substrate bending test <sup>e</sup>	3	12	0
C3	4.3 Mounting <sup>c</sup> 4.4 Visual examination 4.5.1 Leakage current 4.5.2 Capacitance 4.5.3 Tangent of loss angle 4.5.4 Impedance <sup>d</sup> 4.5.5 Equivalent series resistance <sup>d</sup>	3	78 <sup>b)</sup>	0
C3.1	4.8 Shear test 4.10 Rapid change of temperature 4.11 Climatic sequence (Style 1 only)	6	18	0
C3.2	4.12 Damp heat steady state (Style 1 only)	6	9	0
C3.3	4.15 Endurance	3	24	0
C3.4	4.13 Characteristics at high and low temperature	6	15	0
C3.5A	4.14 Surge voltage	12	6	0
C3.5B	4.16 Reverse voltage <sup>d</sup>	12	6	0

<sup>a</sup> Refers to Clause 4 of this specification.  
<sup>b</sup> The values of these measurements serve as initial measurements for the tests of Group 3.  
<sup>c</sup> The specimens found to be non-conforming after mounting shall not be taken into account when calculating the permitted non-conforming items for the following tests. They shall be replaced by spare capacitors.  
<sup>d</sup> If required by the detail specification.  
<sup>e</sup> Not applicable to surface mounting capacitors which according to their detail specification shall be mounted on alumina substrates.

IECNORM.COM  
Click to view the full PDF of IEC 60384-3:2006