

INTERNATIONAL STANDARD

ISO
2575

Seventh edition
2004-05-01

AMENDMENT 3
2008-10-15

Road vehicles — Symbols for controls, indicators and tell-tales

AMENDMENT 3

Véhicules routiers — Symboles pour les commandes, indicateurs et témoins

AMENDMENT 3

STANDARDSISO.COM : Click to view the full PDF of ISO 2575:2004/Amd.3:2008



Reference number
ISO 2575:2004/Amd.3:2008(E)

© ISO 2008

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 3 to ISO 2575:2004 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 13, *Ergonomics applicable to road vehicles*.


STANDARDSISO.COM : Click to view the full PDF of ISO 2575:2004/Amd 3:2008

Road vehicles — Symbols for controls, indicators and tell-tales

AMENDMENT 3

Page 10, Annex A

Add the following symbols to Annex A, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
A.32		Bend lighting	Application of ISO 7000-2669



STANDARDSISO.COM : Click to view the full PDF of ISO 2575:2004/Amd 3:2008

Add the following symbols to Annex C, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
C.21		Glare prevention exterior mirror, horizontal type Symbol is shown for left-hand mirror. Symbol may be used as mirror image for right-hand mirror.	Application of ISO 7000-2674
C.22		Glare prevention exterior mirror, vertical type Symbol is shown for left-hand mirror. Symbol may be used as mirror image for right-hand mirror.	Application of ISO 7000-2673
C.23		Front wiper de-ice electric heating system	Application of ISO 7000-2841
C.24		Windscreen washer fluid heating	Application of ISO 7000-2839

Page 23, Annex D

Add the following symbols to Annex D, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
D.35		Wind draught deflector Symbol shall be outline, cannot be solid.	Application of ISO 7000-2644
D.40		Head restraint fold down	Application of ISO 7000-2842
D.41		Heated steering wheel	Application of ISO 7000-2843


Page 30, Annex F

Add the following symbols to Annex F, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
F.26		Engine emission system temperature	Application of ISO 7000-2844


Page 32, Annex G

Add the following symbols to Annex G, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
G.13		Fuel pressure	Application of ISO 7000-1392





Page 35, Annex H

Add the following symbols to Annex H, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
H.14		Transmission system pressure, road vehicles	Application of ISO 7000-2647

Page 40, Annex I

Add the following symbols to Annex I, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
I.23		Fifth wheel coupling locked/secure The keyhole may be omitted.	Application of ISO 7000-2613
I.24		Fifth wheel coupling unlocked/unsecure The keyhole may be omitted.	Application of ISO 7000-2629
I.26		Axle fluid temperature	Application of ISO 7000-2845
I.27		Drawbar coupling locked/secure The keyhole may be omitted. The drawbar coupling may be changed to better represent the true shape of the coupling device.	Application of ISO 7000-2846
I.28		Drawbar coupling open/unsecure The keyhole may be omitted. The drawbar coupling may be changed to better represent the true shape of the coupling device.	Application of ISO 7000-2847
I.29		Drawbar angle warning Symbol elements shall be in yellow, as specified in ISO 3864-1:2002.	Application of ISO 7000-2850

STANDARDSISO.COM - Click to View Full PDF of ISO 2575:2004/Amd.3:2008

Page 43, Annex J

Add the following symbols to Annex J, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
J.13		Hill descent control	Application of ISO 7000-2648
J.17		Limited performance mode	Application of ISO 7000-2639

Page 46, Annex K

Add the following symbols to Annex K, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
K.17		Side obstacle warning Symbol allows for mirror image, to indicate left-side warning.	Application of ISO 7000-2796
K.18		Side impact airbag off Symbol allows for mirror image.	Application of ISO 7000-2840
K.19		Passenger side impact airbag off Symbol allows for mirror image.	Application of ISO 7000-2848
K.20		Camera	Application of IEC 60417-5116



Page 49, Annex L

Add the following symbols to Annex L, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
L.19		Smart Card, Smart Key	Application of ISO 7000-2849

Page 51, Annex M

Add the following symbols to Annex M, in sequence according to symbol number.

Symbol number	Symbol form/shape	Symbol description/application	ISO/IEC registration number
M.08		Propulsion battery failure	Application of ISO 7000-2653
M.12		Electric motor enabled The left or right arrowhead may be omitted to show direction of movement. To notify that electric propulsion is engaged and that forward and reverse motion is possible.	Application of ISO 7000-2654

Page 52

Insert the following new annex between Annex N and Annex X.