

Connectors, Electrical, Rectangular Crimp Contacts  
General Specification For

## 1. Present Requirement: 6.3 Qualification, Page 52

"With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in applicable qualified products list (QPL) whether or not such products have actually been so listed by that date. The attention of the manufacturers is called to this requirement, and they are urged to arrange to have products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to the qualification of products may be obtained from the Naval Air Warfare Center Aircraft Division Patuxent River, Code 4.4.4, Building 1461, 48256 Shaw Road, Unit 4, Patuxent River, MD 20670."

## Change Requirement: 6.3 Qualification, Page 52

"With respect to products requiring qualification by the government, awards will be made only for products, which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List (QPL), whether such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers (suppliers) are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts for the products delineated in this specification. Qualification is required for U.S. Government procurement. The qualifying activity, for U.S. Department of Defense procurement purposes, is the Naval Air Systems Command (Code 4.4.5.3), 22229 Elmer Road, Bldg. 2360, Room 107, Patuxent River, MD 20670. Application for qualification tests shall be made in accordance with provisions governing qualification in SD-6. Unless otherwise specified by contract, commercial procurement of these products shall meet these requirements."

Rationale for Change: The qualifying activity has requested the paragraph to be changed to establish the correct address and qualification submittal requirements which may be impacting timely procurement of SAE designated components.

**Amendment A1: August 2004**

## 1. Present Requirement: 2.1 Government documents, Page 6 and 13, respectively

MIL-STD-105 Sampling Procedures &amp; Tables for Inspection Attributes

MIL-STD-45662 Calibration System Requirements

MIL-C-26074 Coating, Electroless Nickel, Requirement for

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: [CustomerService@sae.org](mailto:CustomerService@sae.org)  
**SAE WEB ADDRESS:** <http://www.sae.org>

Change Requirement: 2.1 Government documents, Page 6 and 13, respectively

Delete MIL-STD-105, MIL-STD-45662, and MIL-C-26074 references

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456300C60-BS50.93 dated SEP 29 1995, Ser: 456300C60-50.111 dated 1 October 1995, and 10380-444-JRM/m07.07 of SEP 10 1991, respectively.

2. Present Requirement: 2.2 Other publications, Page 13

Not specified

Change Requirement: 2.2 Other publications, Page 13 add after "(Copies-----officer)."

Other publications

The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN NATIONAL STANDARDS INSTITUTE, ANSI/ISO 10012-1 Quality Assurance Requirements for Measuring Equipment (Application for copies should be addressed to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036)

AMERICAN SOCIETY FOR QUALITY CONTROL, ASQC Z1.4, SAMPLING PROCEDURES AND TABLES FOR INSPECTION BY ATTRIBUTES (Application for copies should be addressed to the American Society of Quality Control, PO Box 3005, 611 East Wisconsin Ave, Milwaukee, WI 53201-46004)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), ASTM B 733-90, Nickel-Phosphorous Coatings on Metals (Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL CONFERENCE OF STANDARDS LABORATORIES, NCSL Z540-1, - General Requirements for Calibration Laboratories and Measuring and Test Equipment (Application for copies should be addressed to the National Conference of Standards Laboratories, 1800 30th Street, 305B, Boulder, CO 80301-1032)

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456300C60-BS50.93 dated SEP 29 1995, Ser: 456300C60-50.111 dated 1 October 1995, and 10380-444-JRM/m07.07 of SEP 10 1991.

3. Present Requirement: Section 3.3 Materials, 3.3.4.2 Class 2 "Finish" on Page 14

"Finish --- MIL-C-26074"

Change Requirement: Section 3.3 Materials, 3.3.4.2 Class 2 "Finish" on Page 14

"Finish --- ASTM B 733-90"

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456300C60/50.110-1 dated 1 October 1995.

4. Present Requirement: Section 3.5 Performance, 3.5.8 Mating and unmating forces (connector assembly) on Page 18

"When tested --- shall not exceed 45 pounds per insert. (see 3.5)"

Change Requirement: Section 3.5 Performance, 3.5.8 Mating and unmating forces (connector assembly) on Page 18.  
Add to end of paragraph:

"When tested --- shall not exceed 45 pounds per insert except insert 104. (see 3.5)" For position insert 104, the engagement force prior to test conditioning shall not exceed 65 pounds and after test conditioning shall not exceed 75 pounds. (see 4.6)"

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456100C77DAL-M007009, 21 April 1997

5. Present Requirement: Section 4. QUALITY ASSURANCE PROVISIONS, 4.4.1 "Test equipment and inspection facility", last sentence on Page 19

"The ---- calibration ---- MIL-STD-45662."

Change Requirement: Section 4. QUALITY ASSURANCE PROVISIONS, 4.4.1 "Test equipment and inspection facility", last sentence on Page 19

"Calibration: ---- ANSI/NCSL Z540-1 or ISO 10012-1."

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456300C60-50.111 dated 1 October 1995.

6. Present Requirement: 4.5.1.1.2 Sampling plan, Page 23

"Sampling plan: Statistical sampling and inspection shall be in accordance with MIL-STD-105 for general inspection Level II. The acceptable quality level (AQL) shall be as specified in Table VI. Major and minor defects shall be as specified in MIL-STD-105."

Change Requirement: 4.5.1.1.2 Sampling plan, Page 23

"Sampling plan: A random sample shall be selected from each inspection lot in accordance with Level II of ANSI/ASQC Z1.4 for inspection based on the specified AQL in Table II. Classification of defects shall be as specified in Table II and definitions in herein (see 6.8). A manufacturer's normal quality control tests and production tests may be used to fulfill Group A inspection, provided they at least equal the quality required by Table II."

Rationale for Change: Incorporate Department of the Navy Engineering Position Letter Ser: 456300C60-BS50.93 dated SEP 29 1995

7. Present Requirement: 6.2 Definitions, Page 28

Not required

Change Requirement: 6.2 Definitions, Page 28

"c. CRITICAL DEFECTS - A critical defect is a defect that judgment and experience indicate would result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product, or a defect that judgment and experience indicate is likely to prevent performance of the actual function of a major end item such as a ship, aircraft, tank, missile, or space vehicle.